


Non-Nano Sunscreen featuring GCP55TEL and GC70MZCJ

Formula KSL-169A



Kobo Products - formulations

Part	Percent	Ingredients	INCI Name	Supplier
1	37.63	Deionized Water	Water	
	0.90	Sodium Chloride	Sodium Chloride	Morton Salt
	0.20	Allantoin	Allantoin	RITA Corp
2	20.04	Finsolv® TN	C12-15 Alkyl Benzoate	Finetex
	11.90	GCP55TEL	Titanium Dioxide (And) Caprylic/Capric Triglyceride (And) Alumina (And) Silica (And) Polyhydroxystearic Acid	Kobo Products
	6.62	GC70MZCJ	Zinc Oxide (And) Caprylic/Capric Triglyceride (And) Jojoba Esters (And) Silica	Kobo Products
	3.00	ABIL® WE 09	Polyglyceryl-4 Isostearate (And) Cetyl PEG/PPG-10/1 Dimethicone (And) Hexyl Laurate	Evonik
	3.00	ABIL® Wax 9801	Cetyl Dimethicone	Evonik
	3.00	Cetiol® CC	Dicaprylyl Carbonate	Cognis Corp.
	3.00	Floraesters® 15	Jojoba Esters	Floratch
	2.50	Arlacel P135	PEG-30 Dipolyhydroxystearate	Croda
	1.00	Cetiol® SB 45	Shea Butter	Cognis Corp.
	0.15	Methyl Paraben NF	Methylparaben	International Sourcing
	0.06	Propyl Paraben NF	Propylparaben	International Sourcing
	3	3.00	Aculyn™ 44	PEG-150/Decyl Alcohol/SMDI Copolymer
4	4.00	BPA-515	Polymethyl Methacrylate (And) Isopropyl Titanium Triisostearate	Kobo Products

100

Manufacturing Procedure

- In a double jacketed stainless steel tank equipped with a lightening type mixer along with side sweep action, mix ingredients in Part 1 in the order listed.
- Heat Part 1 to 75°C.
- In a second double jacketed stainless steel tank equipped with a lightening type mixer heat Part 2 to 75°C.
- Add Part 1 to Part 2 very slowly with mixing using a lightening type mixer.
- Cool product slowly down to about to 45°C.
- Add Part 3 to main batch, one ingredient at a time, in the order listed.
- Switch mixing to side sweep.
- Cool emulsion further to 33°C with sweep action mixing.
- Add Part 4 under propeller.
- Homogenize at 4500 rpm for approximately 10 minutes.

Description

This UV Balanced sunscreen uses Kobo's Non-Nano TiO₂ dispersion, GCP55TEL and Non-Nano ZnO dispersion, GC70MZCJ. These Non-Nano dispersions give a high SPF/UVA ratio. BPA-515 is an ITT treated sphere that gives excellent slip and non tacky drydown film on skin.

Notes

Active Ingredient(s)	
Zinc Oxide	4.50%
Titanium Dioxide	6.00%

SPF testing: in vivo on 3 subjects

Kobo Products, Inc.

3474 South Clinton Avenue, South Plainfield, NJ 07080 - USA
tel: +1 - 908-757-0033 fax: +1 - 908-757-0905 info@koboproductsinc.com

March, 2010

KOBO

www.koboproducts.com

Formulations

Product formulations are included as illustrative examples only. Kobo Products Inc. makes no representation or warranty concerning the efficacy or safety of any product manufactured using such formulations. All statements concerning the possible use of Kobo Products Inc. are for research purposes only. Responsibility for the performance or adequate testing of any product prior to sale or use of any such product lies with the manufacturer thereof.

Use of Products

Products sold by Kobo are designed, manufactured and sold for industrial use only. Prior to use of any such product for any application other than an industrial use, the user has the sole responsibility and obligation to determine the suitability of any such product for any such application.

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute a permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Limitation of Liability

Kobo Products Inc. shall in no event, whether the claim is based on warranty, contract, tort, strict liability, negligence or otherwise, be liable for incidental or consequential damages, or for any other damages in excess of the amount of the purchase price.

The Powder & Dispersion Specialist

KOBO
www.koboproducts.com

Kobo Products, Inc.

3474 South Clinton Avenue
South Plainfield, NJ 07080 - USA
tel : +1 - 908-757-0033
fax : +1 - 908-757-0905

Kobo Products SAS

Rue Buissonnière. BP 67660
31676 Labege Cedex - FRANCE
tel : +33 - (0)5-62-88-77-40
fax : +33 - (0)5-62-88-77-49